


多功能半自動打印機 LIP-280

Multi-Purpose Semi-Automatic Printer



優點:

1. 此種轉印方式可保持被打印物表面上之光澤
2. 不使凸板直接打在印刷物上可保持凸板和印刷物之不受損傷
3. 若被打印物表面不平 亦可得到平面轉印之效果
4. 操作者兩手皆可交換印刷源 能減少疲勞 提高工作效率

印版

1. 印版之安裝台為磁鐵石 故鋼底之合成樹脂版可以簡單吸著於上.
2. 鋅凸版或橡皮版則用兩面接著膠帶裝

適用種類 :排條式

1. 塑膠膜電容器, 金屬化膜電容器, 陶瓷電容器, 鉭質電容器, 電晶體, 排條電阻, 突波接收器 等

規格:

生產速度: 最高速每小時 800 支

電源: 110V- 220V

機台尺寸: 825 x 410 x 1000 mm

Advantage/Merit

1. This transfer printing method will remain the quality of gloss of the printing surface
2. A relief printing rubber plate does not directly contact to printing article which preventing both parts not to damage each other.
3. Even the printing article with the uneven surface the printing quality still remains.
4. Operator could use both hands to exchange the printing article that not only reduce the weary also enhancement-working efficiency.

Printing plate

1. Printing plate install bed has build with magnet it easy for synthetic resin printing plate with steel bottom.
2. Use twin adhesive tape for zinc relief printing or the rubber plate.

Suitable type: Row of strip type.

1. Mylar capacitor, the metallize film capacitor, ceramic capacitor, the tantalum capacitors, transistor, arranges the strip resistance, varistor... and so on.

Spec

Production speed: each hour 800

Power: 110/220VAC

Size: 825 x 410 x 1000mm